

SONOREX TECHNIK

RM 16.2 - Module series

High-power ultrasonic baths and rinsing baths
for aqueous liquids

RM 16.2 UH:	Ultrasonic bath with heating
RM 16.2 U:	Ultrasonic bath without heating
RM 16.2 H:	Rinsing bath with heating, without ultrasound
RM 16.2:	Rinsing bath without heating, without ultrasound



RM 16.2 UH

	RM 16.2 UH	RM 16.2 U	RM 16.2 H	RM 16.2
Code No.	8204	8205	8206	8207

Oscillating tank / rinsing tank

Internal dimensions, l × w × d	325 × 275 × 200/210* mm, *inclined tank bottom		
Filling level mark from the tank bottom	135 mm		
Upper edge overflow gutter from the tank bottom	150 mm		
Tank edges	rectangular form		
Capacity	20 l		
Operating volume up to filling level mark	13 l		
Filling volume to overflow gutter	14 l		
Tank material	stainless steel AISI 316L, 2 mm, welded		
Outlet / Inlet	3-way ball valve G ½ incl. hose and hose sockets, on the left side; brass, galvanically coated		
Overflow, tightly welded	with closing cap G 1, at the rear side		
Overflow gutter	at the rear side		
Tank bottom	inclined		

Ultrasound

Ultrasonic peak power corresponds to 4 times ultrasonic nominal power	1200 W	-
Ultrasonic nominal power	300 W	-
Ultrasonic frequency	40 kHz	-
Pulse function	✓	-
Sweep	✓	-
Oscillating systems	6 pieces at tank bottom	-
Control	turning knob	-
Time setting	1 – 15 min and continuous operation	-

	RM 16.2 UH	RM 16.2 U	RM 16.2 H	RM 16.2
--	------------	-----------	-----------	---------

Temperature control

Heating, thermostatically adjustable	30 – 80 °C	-	30 – 80 °C	-
Heating power	800 W	-	800 W	-

Housing

External dimensions, l x w x h	365 x 340 x 390 mm			
Housing material	stainless steel AISI 304			
Handles	on the sides			
Degree of protection	IP 32			
Feet	4 rubber feet			

Power supply

Mains supply	230 V~ (± 10 %), 50/60 Hz			
Power consumption	1.1 kW	0.3 kW	0.8 kW	-
Current consumption	4.8 A	1.4 A	3.5 A	-
Leakage current	< 3.5 mA	< 3.5 mA	< 3.5 mA	-
Mains cable	2 m, fixed at the unit, with EU plug CEE 7/7 (type E+F)			

Environmental conditions


Permissible ambient temperature	5 – 40 °C			
Permissible relative humidity to 31 degree	80 %			
Permissible relative humidity to 40 degree	50 %			

Shipping information

Weight net gross	17 kg 21 kg	16 kg 20 kg	15 kg 19 kg	14 kg 17 kg
Packing, l x w x h	1 carton, 475 x 445 x 465 mm			

Accessories

Type	Code No.	Description
MK 16 B	8408	insert basket, stainless steel also applicable for lifting device MB and oscillation MO load up to 10 kg internal dimensions 275 x 245 x 50 mm, l x w x d mesh size 5 x 5 mm
MD 16	8440	lid, stainless steel
TB 16	8400	drop plate, stainless steel, between two tanks



Supplementary equipment

MO 16.2	8306	oscillation
WO 16-1	8656	rack for 1 tank, in connection with MO 16.2
WO 16-2	8657	rack for 2 tanks, in connection with MO 16.2
WO 16-3	8658	rack for 3 tanks, in connection with MO 16.2
WO 16-4	8659	rack for 4 tanks, in connection with MO 16.2
WG 16-2	8506	rack for 2 tanks, in connection with MB 16
WG 16-3	8500	rack for 3 tanks, in connection with MB 16
WG 16-4	8507	rack for 4 tanks, in connection with MB 16
MB 16	8300	lifting device with oscillation, in connection with WG 16
KV 16	8450	cascade tube between two tanks



WO 16-3



WG 16-4



MB 16 with WG 16-4



Peripheral units

Type	Code No.	Description
FA 16	8606	filtration with pre- and main filter incl. connection kit
OX 16	8600A	oil separator incl. connection kit
WA 16	8632A	DI-water-preparation device incl. connection kit
TO 16	8334	trough dryer, internal dimensions 500 x 300 x 350 mm, l x w x d



Caution!
Do not use combustible liquids, acids, chemicals containing chloride ions and household cleaners.
Do not place items on the tank bottom.
Recommendation: Special cleaning agents TICKOPUR



Distributed by:

A.D. Jansen Zwolle B.V.
Faradaystraat 21
8013PH Zwolle - NL

Tel: +31 (0) 384550646
klantenservice@djaky.com
www.djaky.com

Subject to technical alterations without notice. Dimensions subject to production tolerances.
Illustrations exemplary, not true to scale. Decoration products are not included in delivery.

2368 GB/2020-01

BANDELIN electronic GmbH & Co. KG
Heinrichstraße 3 – 4
12207 Berlin
Deutschland

www.bandelin.com
info@bandelin.com
☎ : +49 30 768 80-0
☎ : +49 30 773 46 99

Zertifiziert nach
ISO 9001
ISO 13485